## Eliminator Next Gen

## 2" and 4" Display Setup Instructions

<u>WARNING</u>: Only use the supplied cable to connect the Eliminator Next Gen to the LED display. Using any other cable may damage the display or the Eliminator Next Gen.

- 1. Plug in the LED Display 110 volt wall adaptor. Connect one end of the supplied display communication cable to the port on the LED display. Connect the other end of the cable to the Eliminator Next Gen LED display port (second port from the left on the top of the unit)
- 2. Power the Eliminator Next Gen using the AC adaptor supplied with the unit. If on battery power, press and hold the right "STAGE" button on the front of the unit to turn on.
- 3. Press the Left Arrow Button until "Setup" is displayed
- 4. Press the "Setup" icon to enter the Setup menu
- 5. Press the slider to the right of "LED Sign" until it reads "On"
- 6. Please perform the following depending on your display size
  - a. **2" LED Display:** Press the box to the right of "Sign Type" Select "Portatree-2"
  - b. **4" LED Display:** Press the box to the right of "Sign Type" Select "Portatree-4" for new displays Select "Betabrite" for older displays
- Press "Return" to save the display settings. The Eliminator Next Gen will display "Initializing Display." The display will go through an initialization sequence. The display will read "Sign Ready" when complete.

